

Satellite Irradiance Models and Datasets

Adam Kankiewicz Solar Resource Specialist 2014 PV Sandia Performance Modeling Workshop May 5, 2014



Agenda

- The Evolution of Solar Irradiance Modeling and Datasets
- Satellite-based Irradiance Modeling
- TMY Data Considerations
- Which Data Should I Use?




Agenda

- The Evolution of Solar Irradiance Modeling and Datasets
- Satellite-based Irradiance Modeling
- TMY Data Considerations
- Which Data Should I Use?



The Origins of TMY



ABSTRACT

The Test Reference Year (TRY) for a specified location is a data collection consisting of 8760 sets of hourly weather data. Its main objection is to provide data for computerized calculations regarding energy conservation, energy consumption in buildings, and indoor dimate.

This report commends a enitable formula TRY, describes which weather data are mandatory the main objective, and recommends how is report does not recommend any specific proselecting a TRY for a given location.

"It's main objective is to provide data for computerized calculations regarding energy conservation, energy consumption in buildings and indoor climate."

What is TMY?

- Year long file of hourly ("8760") weather data pulled from a bank of longer historical data coverage
- Meant to typify average weather conditions at a location (P50)
- TMY data are consistent at the monthly level
- Current NREL NSRDB TMY2 and TMY3 weighting scheme:

GHI: 25%


DNI: 25%

Met data (T, Td, WS): 50%



What is TGY?

- Typical GHI Year (TGY)
- Same concept as TMY but with weighting based solely on GHI






The Evolution of Irradiance Modeling

Model	METSTAT	Sa	Satellite-based		
Methodology	Typical Meteorogical Year (TMY)			Typical Yea (TG	ar
Dataset	TMY2	TMY3	SUNY Satellite	TGY	Updated Satellite
	1970's				2014

Modeling Surface Irradiance Data





Primary difference is how clouds are observed and handled!

Agenda

- The Evolution of Solar Irradiance Modeling and Datasets
- Satellite-based Irradiance Modeling
- TMY Data Considerations
- Which Data Should I Use?



Satellite Model Components


Radiative Transfer Model (quasi-physical)

+

Cloud Modulation (largely empirical)




Radiative Transfer Model






Model Sensitivities



W Precipitable waterO₃ OzoneH Altitude



What GOES into a Satellite Model?


Radiative Transfer Model (quasi-physical)

+


Cloud Modulation (largely empirical)



Cloud Modulation




Cloud Modulation



DARK (clear)

WHITE (cloudy)


DNI Extrapolation with DIRINDEX



DARK (clear)


WHITE (cloudy)

Specular Reflectivity Must Be Accounted for






Snow Must Be Accounted for




DARK (clear)

WHITE (cloudy)




Visible Channel

IR Channel Combination






Visible + IR: Better Snow Discrimination






Visible + IR: Better Snow Discrimination

Visible Model



Visible + IR Model



Monthly Average Global Horizontal Irradiance (W/m²)


February 2011



Low

High

Satellite Model Error Characteristics



Agenda

- The Evolution of Solar Irradiance Modeling and Datasets
- Satellite-based Irradiance Modeling
- TMY Data Considerations
- Which Data Should I Use?



TMY3 Data Locations (All Classes)






Not All TMY3 Locations Are Created Equal

	% of Sites	Uncertainty	# of Years Sampled (Generally)
Class I	16%	Lowest	24 years
Class II	43%	Higher	12 years
Class III	41%	Highest	12 years + missing data

Only 40 sites have measured solar data (<2%)
Pre-1998 = METSTAT modeled
1998-2005 years = Satellite modeled

TMY3 Data Locations (Class Differences)


Minneapolis/St. Paul Example



- TMY3_Minneapolis-St. Paul Int. Airport (Class I)
- TMY3_St. Paul downtown Airport (Class II)
- TMY3_Minneapolis/Crystal (Class II)

TMY3 Data Locations (Class Differences)

Minneapolis/St. Paul Example



TMY3 Minneapolis/Crystal	Class II
TMY3 St. Paul Downtown Airport	Class II
TMY3 Minneapolis/St. Paul Airport	Class I


SolarAnywhere Satellite

TMY3 Data Locations (Class I)






TMY3 (Class I) and Satellite-based Data





Error as a Function of Distance



Agenda

- The Evolution of Solar Irradiance Modeling and Datasets
- Satellite-based Irradiance Modeling
- TMY Data Considerations
- Which Data Should I Use?




Which Dataset Should I Use?

Use Cases	TMY/ TGY	Ground	Satellite
Initial Estimates	\checkmark		
Siting & Financing of Utility Scale PV Systems		\checkmark	\checkmark
Production Guarantees for DG Lease Funds			\checkmark
Real-time Monitoring		\checkmark	\checkmark




More than One Flavor of Satellite Data

- Spatial Resolution
- Temporal Resolution
- Length of Coverage
- Time-frame
- Tuned/Not-Tuned
- Ancillary Weather Data







Please feel free to contact us for any details or clarification related to presentation

Mark McKahan-Jones Senior Account Executive mmj@cleanpower.com Adam Kankiewicz SolarAnywhere Research Spec. adamk@cleanpower.com Skip Dise SolarAnywhere Prod. Manager johndise@cleanpower.com

